

## With the strongest thread on the planet, they certainly can.

GORE® TENARA® Sewing Thread puts an end to ruptured seams of boat covers. bimini tops, sprayhoods, and other marine fabric applications. Unlike conventional threads, it maintains the strength of the seam even after prolonged exposure to UV rays, salt water, cleaning chemicals or rain.

- \* With unique ePTFE fiber construction
- \* UV. weather and chemical resistant
- \* Does not rot, fade and is non-staining
- \* Guaranteed to last the lifetime of the fabric
- \* Made in the USA

## Clear for for optimal fabric blending:

Part Number	Linear Density	Approximate Polyester Equivalent	Nominal Break Strength	Nominal Elongation at Break (%)	Yield Per Spool	Recommended Needle Size
M1000LTR-L-5	1111 dtex 1000 denier	Nm 50/60 69 Tex	3114 cN 7 lbs	17	2100 m 2300 yds	Nm 90-110 #14-16
M1000KTR-L-5	1556 dtex 1400 denier	Nm 35/40 92 Tex	4448 cN 10 lbs	17	1750 m 1900 yds	Nm 100-120 #18
M1003HTR-L-5	2775 dtex 2500 denier	Nm 20/25 138 Tex	8452 cN 19 lbs	10	1050 m 1150 yds	Nm 120-140 #19-22

## Vibrant and fade-resistant colors:

Part Number	Linear Density	Approximate Polyester Equivalent	Nominal Break Strength	Nominal Elongation at Break (%)	Yield Per Spool	Recommended Needle Size
M1000TR-(XX)-5	1556 dtex 1400 denier	Nm 35/40 92 Tex	3559 cN 8 lbs	17	1750 m 1900 yds	Nm 100-120 #18
M1003HTR-(XX)-5	2775 dtex 2500 denier	Nm 20/25 138 Tex	6228 cN 14 lbs	10	1050 m 1150 vds	Nm 120-140 #19-22

LIGHT GREY SANDSTONE (TN) CHESAPEAKE BAY BLUE (CB)





M1000KTR-L-5-300: Small cone in 1400 denier, min. 300 meters in a spool.

To order, substitute colour code for (XX). For example: M1000TR-BK-5 (1556 dtex/1400 denier Black).

Exclusively available from:



Specialty Fabrics and Accessories info@bvzasia.com www.bvz.com